





C-150e MAX

Quality and performance from global market leader

The Ce-Series provides the ideal solution for operators delivering temperature sensitive cargo in small vehicles. There are four road-only models to suit vehicle bodies up to 34 m3.

- $\boldsymbol{\cdot}$ Reliable protection for fresh and frozen cargo
- High volume airflow for boxes up to 34 m3
- · Highest cooling capacity in its segment
- New controller for error-free operation
- Full Thermo King service and parts support

Dimensions	Unit		Condenser	
Height		227 mm		227 mm
Width		789 mm		789 mm
Depth		500 mm		500 mm

Specifications

Compressor	
Model	QP08N
Displacement	131 cm3
Number of cylinders	6
D. C. 1. (1)	
Refrigerant Charge	2.22.1
Charge	0.62 kg
Refrigeration Capacity	
System net cooling capacity under A.T.P. con	iditions at 30 °C
ambient	
Capacity on engine power 0°C	2080 W
Capacity on engine power -20°C	1090 W
Generic (Boxlength, Refrigerant,)	
Box volume	8 - 16 m3
Refrigerant	R-404A/R-452A
Airflow	745 m3/hr
Controller	CSR
Defrost	
Defrost	Automatic hot gas defrost
	, ,
Heating Capacity	
On the road	1900 W
Weight	
including battery	
Condenser	23 kg
Slimline Evaporator	9 kg
Swash Plate Compressor	,
Swasii Fiate Collipiessoi	6.5 kg

Features and Options				
Life cost management				
ThermoKare Service contracts				
	re & communications			
USB Datalogger TouchPrint data logger				
Datalogger Jr				
Datalogger	_			
	Load Protection			
Bumper feet roof mounting				
HMI holder				
Kit hoses large (upgrade)				
Kit swivel manifold (upgrade)	님			
Hose Cover Muffler kit				
Snow Cover (kit deflector Small)				
Show cover (kit deflector shidil)				
O Not Available	Standard Feature			
Option: Factory Supplied	Option: Dealer Supplied			