

C-250e MAX

Quality and performance from global market leader

The Ce-Series provides the ideal solution for operators delivering temperature sensitive cargo in small vehicles. There are four road-only models to suit vehicle bodies up to 34 m3.

- $\boldsymbol{\cdot}$ Reliable protection for fresh and frozen cargo
- \cdot High volume airflow for boxes up to 34 m3
- Highest cooling capacity in its segment
- New controller for error-free operation
- Full Thermo King service and parts support

Specifications

Commence	
Compressor	0.513
Model	QP13
Displacement	131 cm3
Number of cylinders	6
Refrigerant Charge	
Charge	0.95 kg
Refrigeration Capacity	
System net cooling capacity under A.T.P. cond	litions at 20 °C
ambient	
	2770 W
Capacity on engine power 0°C	2770 W 1460 W
Capacity on engine power -20°C	1460 W
Generic (Boxlength, Refrigerant,)	
Box volume	13 - 22 m3
Refrigerant	R-404A/R-452A
Airflow	1100 m3/hr
Controller	CSR
Controller	CSI
Defrost	
Defrost	Automatic hot gas defrost
Heating Capacity	
On the road	2800 W
Woight	

Weight	
including battery	
Condenser	23 kg
Slimline Evaporator	15 kg
Swash Plate Compressor	6.9 kg

Direct Drive Truck - Single Temperature

Dimensions	Unit	Condens	ser
Height		227 mm	227 mm
Width		789 mm	789 mm
Depth		500 mm	500 mm

Features and Options

Life cost management		
	ThermoKare Service contracts	
re & communications	Data captu	
	USB Datalogger	
	TouchPrint data logger	
	Datalogger Jr	
Load Protection		
	Bumper feet roof mounting	
	HMI holder	
	Kit hoses large (upgrade)	
	Kit swivel manifold (upgrade)	
	Hose Cover	
	Muffler kit	
	Snow Cover (kit deflector Big)	
Standard Feature	O Not Available	
Option: Dealer Supplied	Option: Factory Supplied	