





V-200

Superior temperature control

The V-100, 200 and 300 series offer the optimal temperature control solution for trucks and vans up to 28m3. This ${\color{blue} \textbf{complete range share many common components including}}\\$ the Direct Smart Reefer and has many modular options to fulfill the requirements of every customer with the following benefits:

- · Modern compact platform
- User friendly Direct Smart Reefer Increased reliability
- $\boldsymbol{\cdot}$ Easy maintenance, service and installation

Dimensions	Unit
Height	221 mm
Width	1180 mm
Depth	485 mm

Specifications

Rating

Specifications	
Compressor	
Model	QP13
Displacement	131 cm3
Number of cylinders	6
	1
Refrigerant Charge	
Charge	10: 1.0 20: 1.1 kg
Refrigeration Capacity	
	udiai august 20 °C
System net cooling capacity under A.T.P. columbient	nditions at 30 °C
Capacity on engine power 0°C	2255 W
Capacity on engine power -20°C	945 W
Capacity on electrical stand by 0°C	1850 W
Capacity on electrical stand by -20°C	685 W
Generic (Boxlength, Refrigerant,)	
Box volume	9 - 18 m3
Refrigerant Airflow	R-134a
Controller	1100 m3/hr DSR III
Controller	ווו אכע
Defrost	
Defrost	Automatic hot gas defrost
	·
Weight	
including battery	
Model 30	25 kg
Model 50	75 kg
Installation kit	24 kg
Evaporator	15 kg
Swash Plate Compressor	6.9 kg
Electrical Stand by Motor	
	230/1/50 230/1/60
Voltage / Phase / Frequency	400/3/50 230/3/50
	230/3/60

3.7 kW

Features and Options				
Life cost management				
ThermoKare Service contracts				
Data capture & communications				
USB Datalogger				
TouchPrint data logger				
Wintrac (data analysis software)				
Datalogger Jr				
Load Protection				
Hose extention 2 m/4 m/6 m				
Bumper feet roof mounting				
HMI holder				
Kit hoses large (upgrade)				
Kit swivel manifold (upgrade)				
Din Adapter				
Hose Cover	ñ			
Muffler kit	ī			
Snow Cover (kit deflector Small)				
Snow Cover (kit deflector Big)	O			
Harness Extension 2m/4m/6m				
Door switches				
O Not Available	Standard Feature			
	Option: Dealer			
☐ Option: Factory Supplied	Supplied			