





V-200 MAX

Superior temperature control

The V-100, 200 and 300 series offer the optimal temperature control solution for trucks and vans up to 28m3. This complete range share many common components including the Direct Smart Reefer and has many modular options to fulfill the requirements of every customer with the following benefits:

- · Superior temperature control
- · User friendly Direct Smart Reefer
- Flexibility
- Improved reliability of electrical components
- Ease of maintenance and service
- $\bullet \ \mathsf{Ease} \ \mathsf{of} \ \mathsf{installation}$

Dimensions	Unit
Height	221 mm
Width	1180 mm
Denth	485 mm

Specifications

Compressor	
Model	QP13
Displacement	131 cm3
Number of cylinders	6

Refrigerant Charge	
Charge	10/30: 1.0 20/50: 1.2
Charge	kg

Retrigeration Capacity		
System net cooling capacity under A.T.P. conditions at 30 $^{\circ}\text{C}$ ambient		
Capacity on engine power 0°C	2770 W	
Capacity on engine power -20°C	1460 W	
Capacity on electrical stand by 0°C	1970 W	
Capacity on electrical stand by -20°C	1130 W	

Generic (Boxlength, Refrigerant,)	
Box volume	13 - 22 m3
Refrigerant	R-404A/R-452A
Airflow	1100 m3/hr
Controller	DSR III

Dellost	
Defrost	Automatic hot gas defrost

Heating Capacity	
On the road	2800 W
Electric Stand By Operation	2050 W

Weight	
including battery	
Model 30	25 kg
Model 50	75 kg
Installation kit	24 kg
Evaporator	15 kg
Swash Plate Compressor	6.9 kg

Electrical Stand by Motor	
	230/1/50 230/1/60
Voltage / Phase / Frequency	400/3/50 230/3/50
	230/3/60
Rating	3.7 kW

Fea	tures and Options
	ife cost management
ThermoKare Service contracts	
Data captu	re & communications
USB Datalogger	
TouchPrint data logger	
Wintrac (data analysis software)	
Datalogger Jr	
	Load Protection
Hose extention 2 m/4 m/6 m	
Bumper feet roof mounting	
HMI holder	
Kit hoses large (upgrade)	
Kit swivel manifold (upgrade)	•
Din Adapter	
Hose Cover	
Muffler kit	
Snow Cover (kit deflector Small)	
Snow Cover (kit deflector Big) Harness Extension 2m/4m/6m	
Door switches	
Bool switches	
O Not Available	Standard Feature
Option: Factory Supplied	Option: Dealer
7 11	Supplied