



V-200s MAX

Dimensions	Unit	Condenser
Height	242 mm	242 mm
Width	789 mm	789 mm
Depth	500 mm	500 mm

### Specifications

Compressor	
Model	QP08N
Displacement	131 cm <sup>3</sup>

  

Refrigerant Charge	
Charge	1.1 kg

  

Refrigeration Capacity	
System net cooling capacity under A.T.P. conditions at 30 °C ambient	
Capacity on engine power 0°C	2410 W
Capacity on engine power -20°C	1180 W
Capacity on electrical stand by 0°C	1500 W
Capacity on electrical stand by -20°C	650 W

  

Generic (Boxlength, Refrigerant, ...)	
Box volume	10 - 19 m <sup>3</sup>
Refrigerant	R-404A/R-452A
Airflow	1000 m <sup>3</sup> /hr
Controller	DSR III

  

Heating Capacity	
On the road	2200 W
Electric Stand By Operation	1300 W

  

Weight including battery	
Condenser w/o electric stand-by	25 kg
Condenser with electric stand-by	43 kg
Evaporator	14 kg

  

Engine	
Rating	1.6 kW
no. of cylinders/displacement	6/82 cm <sup>3</sup>

### Features and Options

Life cost management	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

  

Data capture & communications	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

  

Load Protection	
Hose extention 2 m/4 m/6 m	<input type="checkbox"/>
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit hoses large (upgrade)	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Muffler kit	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>
Door switches	<input type="checkbox"/>

  

Not Available       Standard Feature  
 Option: Factory Supplied       Option: Dealer Supplied