



V-800 MAX Spectrum

Superior temperature control

This V-800 MAX Spectrum unit completes the Thermo King multi-temp application offering. It is the most powerful unit in the V-Series Spectrum platform and it is appropriate for trucks up to seven metres long. It offers a choice of three different evaporator configurations (ES400 + ES400, ES600 + 2 x ES150 and ES600 + ES150) to address a variety of customer application and to meet the requirements of two big compartment boxes, be it transversal or longitudinal configurations alike. The V-800 MAX Spectrum is the right alternative for city distribution in big trucks up to 7 metres body lengths.

Specifications

Refrigeration Capacity: Individual Cooling Capacity	
Capacity on engine power ES400 MAX 0°C	5740 W
Capacity on engine power ES400 MAX -20°C	3300 W
Capacity on engine power ES600 MAX 0°C	6765 W
Capacity on engine power ES600 MAX -20°C	3460 W
Capacity on engine power ES150 MAX 0°C	3975 W
Capacity on engine power ES150 MAX -20°C	2270 W
Capacity on engine power 2 X ES150 MAX 0°C	5640 W
Capacity on engine power 2 X ES150 MAX -20°C	2995 W
Capacity on electrical stand by ES400 MAX 0°C	5300 W
Capacity on electrical stand by ES400 MAX -20°C	3010 W
Capacity on electrical stand by ES600 MAX 0°C	6305 W
Capacity on electrical stand by ES600 MAX -20°C	3110 W
Capacity on electrical stand by ES150 MAX 0°C	3850 W
Capacity on electrical stand by ES150 MAX -20°C	2165 W
Capacity on electrical stand by 2 X ES150 MAX 0°C	5045 W
Capacity on electrical stand by 2 X ES150 MAX -20°C	2705 W

Compressor	
Model	QP21
Displacement	215 cm ³
Number of cylinders	10

Refrigerant Charge	
Charge	ES400+ES400: 5.2 -- ES600+ES150: 5.0 -- ES600+2XES150: 5.15 kg

Refrigeration Capacity	
System net cooling capacity under A.T.P. conditions at 30 °C ambient	
Capacity on engine power -20°C	4395 W
Capacity on engine power ES400 MAX+ES400 MAX -20°C	4395 W
Capacity on engine power ES600 MAX+ES150MAX -20°C	3850 W
Capacity on engine power ES600 MAX+2 X ES150MAX -20°C	4300 W
Capacity on electrical stand by -20°C	3595 W
Capacity on electrical stand by ES400 MAX+ES400 MAX -20°C	3595 W
Capacity on electrical stand by ES600 MAX+ES150MAX -20°C	3385 W
Capacity on electrical stand by ES600 MAX+2 X ES150MAX -20°C	3595 W

Generic (Boxlength, Refrigerant, ...)	
Box volume	40 m ³
Refrigerant	R-404A/R-452A
Airflow	1760 m ³ /hr
Controller	DSR III

Defrost	
Defrost	Automatic hot gas defrost

Heating Capacity	
On the road	4500 W
Electric Stand By Operation	4000 W

Airflow	
on high speed engine operation	
ES400+ES400	1760x2 m ³ /hr
ES600 MAX+ES150MAX	2260+890 m ³ /hr
ES600 MAX++2XES150MAX	2260+(2x890) m ³ /hr

Weight	
including battery	
Condenser w/o electric stand-by	100 kg
Condenser with electric stand-by	160 kg
Evaporator ES600 MAX	28 kg
Evaporator ES400 MAX	20 kg
Evaporator 2 X ES150 MAX	25 kg
Evaporator ES150 MAX	12.5 kg
Swash Plate Compressor	8.5 kg

Electrical Stand by Motor	
Voltage / Phase / Frequency	400/3/50 -- 230/3/50 --400/3/60 -- 230/3/60
Rating	8.2 kW

Features and Options

Life cost management	
ThermoKare Service contracts	<input checked="" type="checkbox"/>

Data capture & communications	
USB Datalogger	<input checked="" type="checkbox"/>
TouchPrint data logger	<input checked="" type="checkbox"/>
Wintrac (data analysis software)	<input checked="" type="checkbox"/>
Datalogger Jr	<input checked="" type="checkbox"/>

Load Protection	
Hose extension 2 m/4 m/6 m	<input type="checkbox"/>
Bumper feet roof mounting	<input checked="" type="checkbox"/>
HMI holder	<input checked="" type="checkbox"/>
Kit swivel manifold (upgrade)	<input checked="" type="checkbox"/>
Din Adapter	<input type="checkbox"/>
Hose Cover	<input type="checkbox"/>
Snow Cover (kit deflector Small)	<input type="checkbox"/>
Snow Cover (kit deflector Big)	<input type="checkbox"/>
Harness Extension 2m/4m/6m	<input type="checkbox"/>
Door switches	<input type="checkbox"/>

Not Available Standard Feature
 Option: Factory Supplied Option: Dealer Supplied